

# g Housing Units-Tapered Adapter Piloted Flange Cartridge | DVC26K408S



Bearing No. DVC26K408S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | Imperial                                                                                                               |
| Bearing Number            | 3.90                                                                                                                   |
| Housing Construction      | 2.62                                                                                                                   |
| UPC Code                  | 76 lb34.5 Kg                                                                                                           |
| Shaft Size Type           | 0883450005425<br>0883450005432<br>0883450005456<br>0883450005463<br>0883450005470<br>0883450005487<br>0883450005494 08 |
| Full Timken Part Number   | 0.0040 in0.102 mm                                                                                                      |
| Locking Style             | 4-1/2 in                                                                                                               |
| Y2 - Geometry Factor      | 0.0063 in0.160 mm                                                                                                      |
| Y1 - Geometry Factor      | 0.0079 in0.201 mm                                                                                                      |
| Shaft Tolerance           | 1500 rpm                                                                                                               |
| Shaft Size                | 700 rpm                                                                                                                |
| Pre Install Clearance Min | 400 rpm                                                                                                                |
| Pre Install Clearance Max | Tapered Adapter                                                                                                        |