

# loyal Bearing Housed Units-Double Concentric Hanger Block | QAAMH18A307S



Bearing No. QAAMH18A307S

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Weight                    | 3-7/16 in                                                                                                              |
| Bearing Number            | 4.31                                                                                                                   |
| Housing Construction      | 2.90                                                                                                                   |
| UPC Code                  | 36 lb16.30 Kg                                                                                                          |
| Shaft Size Type           | 0883450413565<br>0883450413572<br>0883450413589<br>0883450413596<br>0883450413602<br>0883450413619<br>0883450413626 08 |
| Full Timken Part Number   | 1 1/4-7UNC                                                                                                             |
| Locking Style             | 0.0030 in0.076 mm                                                                                                      |
| Y2 - Geometry Factor      | Imperial                                                                                                               |
| Y1 - Geometry Factor      | 0.0024 in0.060 mm                                                                                                      |
| Shaft Tolerance           | 0.0039 in0.100 mm                                                                                                      |
| Shaft Size                | 2400 rpm                                                                                                               |
| Pre Install Clearance Min | 1400 rpm                                                                                                               |
| Pre Install Clearance Max | 1000 rpm                                                                                                               |